

Statement of Evidence:

G011

North Quarter Corner of Section 1, Township 37 North, Range 30 West, 4th Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1849 Original US General Land Office surveyor, Theodore Conkey, set a wood post at this location and bearing trees were recorded.

10" W. Birch	S 83 W	84 links
6" W Birch	S 58 E	40 links

Line trees were noted as a 12" W Birch, East, 19.70 chains and a 12" W Ash, West, 20.33 chains.

Undated County Surveyor's Record Book 1, page 387, lists ties to an iron:

18" Twin Willow	N	115.5
8" W. Oak	SW	139.6

1991 William Lunser, LS 9394, set a cast iron monument at the intersection of a fence line south and a field line north and a centerline of road east/west. He filed a Certificate of Location (Doc. #234185) and notes distances of 2691.66 feet to the NW corner and 2691.42 feet to the NE corner.

2008 Westwood Professional Services Inc. found a cast iron monument at the intersection of a fence line south and a field line north and a centerline of road east/west.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 164333.887
E- 508375.511

2010 The Benton County Surveyor's Office found the cast iron monument. The twin willow and white oak tie trees from Book 1, page 387 were searched for and not found. Since the cast iron monument fits a split of the distance within 0.1 feet and falls at the intersection of the east-west centerline of 115th Street and a fence to the south, it is accepted as marking the obliterated corner position. The 2008 coordinates were verified and reference ties were established as shown.