

Statement of Evidence:

G091

North Quarter Corner of Section 9, Township 37 North, Range 30 West, 4th Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1852 Original US General Land Office surveyor, Edwin James, established corner marked by a wood post with bearing trees noted as.

12" Bur Oak	N 89 1/2 W	842 links
8" Bur Oak	S 87 W	887 links

1935 County Engineer's Notebook No. 94 contains survey for SAR No. 2 running south to north on $\frac{1}{4}$ line. Notes corner as a stone. Ties:

TP	W	28.5
FP	NW	42.0

1962 County Surveyor's Record Book 1, page 403, notes the following reference ties to a stone:

TP	W	48.0
PP	NE	34.6
TP	SW	72.4

(Notebook No. 94 notes the same information showing stone found.)

1992 Paul Wellen, LS 10461, found a fieldstone at the intersection of roads north/south and a fence line east. He replaced it with a cast iron monument and filed Certificate of Location (#216292).

2003 Survey by Sidney Williamson, LS 10918, shows CIM found at corner with a distance of 2666.97 feet to the NE corner of Section 9.

2007 Westwood Professional Services found and located a CIM

2008 The County Surveyor's Office searched and found Wellen's 1992 cast iron monument along the north-south centerline of County Road 58. Distances to the NW and NE Corners gives 2665.13 ft. and 2666.90 ft., respectively. Wellen's cast iron is accepted as marking the best evidence and ties were updated.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 158819.432

E- 492448.879