

Statement of Evidence:

G201

North Quarter Corner of Section 20, Township 37 North, Range 30 West, Mayhew Lake Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

36" Bur Oak	N 32 W	36 links
13" Bur Oak	S 32 E	8 links

1939 County Engineer's Notebook No. 158 contains road survey for CAR No. 20 running from the east along the section line and then north. Corner is shown as an iron pipe at the PI of the road. Ties:

18" Ash	SE	41.0
12" W. Oak	S	67.5

Stationing gives distances of 2659.8 feet to the NE corner.

1959 Notebook No. 158 lists new ties:

PP	SE	47.1'
Twin W. Oak	W	37.1'

1977 Paul Wollen, LS 10461, found a 1/2" iron monument at the P.I. of the road north and east and a fence corner. Filed Certificate of Location (Doc. No. 147251).
Ties to possible 1959 ties:

PP	SE	46.32'
10" Twin W. Oak	W	37.51'

2001 Westwood Professional Services, Inc. found a 1" iron pipe at the P.I. of the road north and east. A cast iron monument was set at the location of a found/removed 1" X 24" open iron pipe.

2006 The Benton County Surveyor's Office found a CIM at the PI of roads north and east. The CIM fits government distances east and west within 2 feet and a split of the distances within 2 feet, though south of a line between section corners by 59 feet. The CIM is accepted as marking the obliterated corner position. Reference ties were established and GPS coordinates were obtained.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-148083.722
E-486968.107