

Statement of Evidence:

G241

North Quarter Corner of Section 24, Township 37 North, Range 30 West, 4th Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded

8" Aspen	N 85 E	9 links
8" Aspen	S 85 W	15 links

1939 County Engineer's Notebook No. 158 contains road survey for CAR No. 20 running east to west along the section line. Corner is shown as a spike set in center of road with fence north. Ties:

Twin 6" W. Oaks	N	66.95'
12" W. Oak	SW	68.5'
FP	SW	42.3'

Stationing gives distances of 2646.2 feet to the NE corner and 2637.2 feet to the NW corner with a delta angle of 0-40' right.

1999 William Lunser, LS No. 9394, found no evidence of a monument and accepted road alignments as evidence of the obliterated corner position and set a RR Spike at the centerline of a township road extension from the south and the centerline of a road east/west for the corner. He filed a Certificate of Location (#283106). He notes a distance of 2658.98 feet to the NE Corner Sec 24, 2623.86 feet to the NW Corner Sec 24 and 5361.62 feet to the South 1/4 Corner Sec 24.

NOTE: 1939 position for assumed quarter corner falls 13 feet west of corner set in 1999. Further analysis and field investigation is needed.

2009 The County Surveyor's Office found a railroad spike fitting the 1999 information, 13 feet west of the 1939 assumed position. Further searching needs to be done for the fence north and ties called for in 1939.

Coordinates Obtained by GPS to railroad spike
NAD 83 (1996 Adjustment)
N-148113.907
E-508142.261

2010 The County Surveyor's Office set a 1/2" x 14" iron pipe capped 19552 from the 1939 information falling on an old fence to the north.

Coordinates Obtained by GPS to Quarter Corner
NAD 83 (1996 Adjustment)
N-148113.218
E- 508155.199