

Statement of Evidence:

G261

North Quarter Corner of Section 26, Township 37 North, Range 30 West, 4th Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1852 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as.

5" Aspen	S 44 W	6 links
6" Aspen	N 45 1/2 W	7 links

1890 County Road Book, page 32, contains Surveyor's Report by Felix Parrent stating road laid out on section line west and east from this corner. Gives 79.28 chains for the north line of Section 26.

2002 No other resurvey information was found on this corner in the Benton County records.

2008 The Benton County Surveyor's Office found a 1/2" open iron pipe in the east-west centerline of 75TH Street Northeast and on a field line to the north. The distance to the northwest corner is 2622.87 feet and the distance to the northeast corner is 2621.34 feet. The overall mile measures about 12 feet long of Mr. Parent's distance from 1890, though fitting a split of the distance within less than a foot. The iron pipe is accepted as marking the obliterated corner position.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 142777.647
E- 502782.411

2009 The Benton County Surveyor's Office found a 1/2" iron pipe with broken cap down 0.7 feet below the road surface. The 2008 coordinates were verified.