

Statement of Evidence:

G321

North Quarter Corner of Section 32, Township 37 North, Range 30 West, Mayhew Lake Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

5" Blk. Oak	N 15 1/2 W	94 links
5" Blk. Oak	S 70 E	92 links

1926 County Engineer's notebook No. 51 and road alignment maps show that the corner is at the intersection of the centerline of an east/west road and a fence line from the south and a barn 48 feet north. It also shows a distance of 2685.6 feet to the NE corner Sec 32 and a distance of 2690.8 feet to the NE corner Sec 31 and no delta angle.

1980 Paul Wollen, LS 10461, set a cast iron monument at the intersection of the centerlines of County Road 4 (running east and west) and a tree line (from the south) and established reference ties. A Certificate of Location (#160206) was filed. A distance of 2696.36 feet was noted to the NW Corner of Section 32 and a distance of 2722.04 feet was noted to the NE Corner of Section 32.

2002 Westwood Professional Services, Inc. found a cast iron monument at the intersection of the centerlines of CSAH No. 4 (running east and west) and a tree line (from the south). We located it using GPS prior to road reconstruction and found that the delta angle was 00-01-58 Rt (moving east to west) and that the distance to the NE Cor Sec 31 is 2696.43 feet and that the distance to the NE Cor Sec 32 is 2721.98 feet. Comparison to 1926 stationing fits within 3 feet of the CIM.
County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-137493.798
E-486675.621

2003 Westwood Professional Services, Inc. set a PK nail at centerline C.S.A.H. #4 in bituminous over cast iron monument.
NAD 83 (1996 Adjustment)
N-137493.798
E-486675.621