

**Statement of Evidence:**

**G032**

Northeast Corner of Section 3, Township 37 North, Range 30 West, 4<sup>th</sup> Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1849 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as.

10" Poplar	N30 E	42 links
6" Poplar	N 23 W	9 links
8" Black Oak	S 32 W	14 links
6" Black Oak	S 18 E	54 links

Line trees were noted as a 12" W Oak, East, 20.76 chains, and a 6" Poplar, West, 20.80 chains.

1938 County Engineer's Notebook No. 122 contains a road survey for CAR 24 running north to south. Notes show corner marked by an iron monument in intersection of roads. Ties to grade stakes SE and NE.

1971 County Surveyor's Record Book 1, page 391, shows iron at corner with ties:

PP	SW	58.85
PP	NE	50.9

(Notation in Notebook No. 122 shows iron found.)

1977 Paul Wollen, LS 10461, notes found iron monument and measured 2715.27 feet to the East ¼ corner of Section 34.

2002 Westwood Professional Services, Inc. found a cast iron monument in road intersection that fit 1971 ties to nail and discs marked "TIE BCHD".

PP	SW	58.92
PP	NE	50.85

2008 Westwood Professional Services, Inc. found a cast iron monument in road intersection.

Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 164406.589  
E- 500399.738

2010 The Benton County Surveyor's Office found the cast iron monument as noted in 2002 and 2008. The power pole ties still remain and the 2002 distances to the power poles were verified. The distance north to a CIM at the east quarter measures 2715.11, fitting the 1977 measurement. It appears that the iron monument from 1938 was found in 1971 and based on ties, it appears that the current CIM perpetuates the 1971 position. The CIM is accepted as marking the obliterated corner position. The 2008 coordinates were verified and reference ties were established as shown.