

**Statement of Evidence:**

**G042**

Northeast Corner of Section 4, Township 37 North, Range 30 West, 4<sup>th</sup> Principal Meridian, (Mayhew Lake Township) Benton County, Minnesota.

1849 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as.

12" Bur Oak	N 69 E	169 links
6" Bur Oak	N 76 W	80 links
12" Bur Oak	S 41 E	46 links

1891 County Road Book, page 16, shows road laid out by Felix Parrant from the west and terminating at this corner.

No Date County Surveyor's Record Book 1, page 393, shows a Granite Monument with ties:

7" W. Oak	SE	144.7
16" Ash	SE	248.2

1957 County Engineer's Notebook No. 94 contains notes corner as a granite monument. Ties:

PP	NE	43.05
Guy Pole	SE	45.9
TP	SW	42.15

1977 Survey by Paul Wellen, LS10461, notes a stone corner in place with a distance of 2695.95 feet to the East 1/4 corner of Section 33.

1983 Certificate of Location filed by David Regan, LS No. 12236, shows he found a 6" x 6" stone monument. Same ties as 1957.

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) on a Cast Iron Monument:

N-164360.591  
E-495051.475

2008 Westwood Professional Services Inc. found a cast iron monument at the centerline of roads north/west/east. Ties noted on the Certificate of Location Doc. # 167991 were checked and found correct.

Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 164360.733  
E- 495050.961