

**Statement of Evidence:**

**G062**

Northeast Corner of Section 6, Township 37 North, Range 30 West, 4<sup>th</sup> Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1849 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as.

4" Blk Oak	N 14 E	250 links
8" Blk Oak	S 74 W	309 links
4" Blk Oak	S 64 E	236 links

1923 County Engineer's Notebook No. 40 contains a survey for CAR No. 1 running south to north. Notes corner marked by an iron with ties:

18" Oak	SW	35.2'
10" Oak	NW	32.6'

Notation shows stone monument with ties:

Cor FP	SW	25.5'
Cor FP	NW	30.0'

Stationing gives distances of 2826.4 feet to the East 1/4 corner of Section 6 and 2693.1 feet to the East 1/4 corner Section 31 with a deflection angle of 0-32' right (running south to north).

County Surveyor's Record Book 1, page 397, notes ties to a granite monument:

18" Oak	SW	35.2
10" Oak	NW	32.6
10" Oak	E	64.8
15" Elm	NE	60.2

1938 County Engineer's Notebook No. 116 contains a survey for SAR No. 1 that notes the following ties to a granite monument in road with town roads west and east:

10" Oak	E	64.8
15" Elm	NE	60.2

Stationing gives distances of 2828.1 feet to the East 1/4 corner of Section 6 and 2695.9 feet to the East 1/4 corner of Section 31.

1977 County Engineer's ties to a granite monument:

12" Oak	SW	119.00
30" Elm	NE	119.35
SW Cor Bld Foundation	NE	128.68

2008 Westwood Professional Services Inc. found a cast iron monument at the centerline of north/east/south/ roads. CIM fit reasonably with 1977 ties.

Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 164326.342

E- 484360.861