

Statement of Evidence:

G222

Northeast Corner of Section 22, Township 37 North, Range 30 West, 4th Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Aspen	N 47 W	190 links
8" Bur Oak	S 55 3/4 E	152 links

1938 County Engineer's Notebook No. 122 contains a road survey for CAR 24 running north to south. Notes show corner marked by a hub set in town road intersection. Ties to hubs NW and SW. 1939 ties:

PWA sign board	NE	43.3
PP	NW	56.6

1939 County Engineer's Notebook No. 158 contains road survey for CAR No. 20 running east to west along the section line. Corner is shown as a hub set in center of road with CAR 24 running north.

1992 Paul Wollen, LS 10461, found a PK Nail at the intersection of the centerlines of County Road 43 (running east and west) and County Road 59 (running north). He replaced it with a cast iron monument and filed a Certificate of Location (#216298).

2008 Westwood Professional Services found a cast iron monument at the intersection of the centerlines of County Road 43 (running east and west) and County Road 59 (running north).

Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 148130.903

E- 500244.899

2009 the Benton County Surveyor's Office found a cast iron monument. The monument falls at the intersection of centerlines north and east-west, measuring within 1 foot to the east quarter corner of Section 15 and 2.5 feet to the north quarter of Section 22 of the 1938 distances. The cast iron monument is accepted as the best available evidence of the corner position. The 2008 coordinates were verified.