

Statement of Evidence:

Northeast Corner of Section 31, Township 37 North, Range 30 West, Mayhew Lake Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

6" Aspen	S 7 W	132 links
6" Aspen	S 1 E	132 links

1926 County Engineer's notebook No. 51 and road alignment shows the following reference ties (also shown in the County Surveyor's Record Book 1, page 447) and notes a distance of 2626.2 feet to the North ¼ corner Sec 31 and a distance of 2690.8 feet to the North ¼ corner Sec 32 and also a delta angle of 0-36 Lt (moving from east to west).

Corner F.P.	S	32.6
F.P.	SE	32.5

Notes show fence line south.

1980 Paul Wollen, LS 10461, found a red-head nail at the intersection of the centerline of County Road 4 (running east and west) and a fence line (from the south). He set a cast iron monument at the position and established reference ties. A Certificate of Location (#160204) was filed.

2002 Westwood Professional Services, Inc. found a cast iron monument at the centerline of CSAH No. 4 (running east and west) and located it using GPS prior to reconstruction of CSAH No. 4. We found that the delta angle is 00-34-17 Lt (moving east to west) and the distance to the North ¼ corner Sec 31 is 2617.06 feet and the distance to the North ¼ corner Sec 32 is 2696.43 feet. Comparison to 1926 stationing fits within 3 feet of the CIM.
County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-137501.187
E-483979.206

2004 Westwood Professional Services, Inc. set a PK nail and disc

NAD 83 (1996 Adjustment)
N-
E-