

**Statement of Evidence:**

**G342**

Northeast Corner of Section 34, Township 37 North, Range 30 West, Mayhew Lake Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

- 1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

14" Burr Oak	S 58 E	120 links
--------------	--------	-----------

16" Burr Oak	N 68 E	119 links
--------------	--------	-----------

- 1890 County Road Book, page 32, contains Surveyor's Report by Felix Parent stating road laid out on section lines south and north from this corner.

- 1926 County Engineer's notebook No. 51 and road alignment maps by H. G. Elletson show the following reference ties to an iron pipe in road intersection.

T.P.	NE	43.5
------	----	------

F.P.	SE	43.6
------	----	------

FP	SW	35.0
----	----	------

A distance of 2629.6 feet was noted to the North ¼ corner Sec 35 and a distance of 2662.7 feet was noted to the North ¼ corner Sec 34. A delta angle of 03-26 Lt, going from east to west, was noted.

- 1961 County Surveyor's Record Book 1, page 453, notes an iron pipe at the corner with the following reference ties.

Top CL W. end cattle pass	SW	50.3
---------------------------	----	------

Top CL E. end cattle pass	SE	49.9
---------------------------	----	------

T.P.	SE	52.8
------	----	------

Corner F.P.	SW	46.3
-------------	----	------

- 1990 Paul Wellen, LS 10461, searched for 1961 iron, but did not find. He set a cast iron monument at the intersection of the centerlines of 55<sup>th</sup> Avenue NE (running north and south) and County Road 4 (running east and west). A Certificate of Location (#201466) was filed.

- 2001 William Lunser, LS 9394, notes a distance of 2663.15 feet to the North ¼ corner of Section 34 per Certificate of Location (#283104).

- 2002 Westwood Professional Services, Inc. found a cast iron monument at the intersection of the centerlines of County Road 4 (running east and west) and 55<sup>th</sup> Avenue NE (running north and south). We located the monument and found that the delta angle is 03-25-22 Lt (moving east to west) and distances were 2663.25 feet to the North ¼ corner Sec 34 and 2630.75 feet to the North ¼ corner Sec 35. CIM fit 1961 ties to the cattle pass.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-137539.332

E-500049.440

- 2004 Westwood Professional Services, Inc. set a PK nail and disc over found a cast iron monument found at the intersection of the centerlines of County Road 4 (running east and west) and 55<sup>th</sup> Avenue NE (running north and south).

NAD 83 (1996 Adjustment)

N-137539.332

E-500049.440