

Statement of Evidence:

East Quarter Corner of Section 26, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

14" Sugar	S 37 1/2 W	9 links
10" Lind	S 78 1/2 E	29 links

1902 County Surveyor's Record Book 2, page 436, and Record Book A, Map No. 30 shows a survey of Section 25 by John Whilt and Map No. 32 shows a survey of Section 26 by John Whilt. Both surveys show corner established midway between section corners with a distance of 79.04 chains (5216.64 feet) for the mile.

1932 County Engineer's Notebook No. 80 for survey of SAR 9 running south to north. Corner is shown as a hub in center of road with fence line west. Stationing gives distances of 2624.6 feet to the SE corner and 2616.6 feet to the NE corner with a delta angle of 0-20' left. Ties:

24" Elm	SW	83.6'
8" Pop.	NW	42.0'

1961 County Engineer's Notebook No. 234 contains survey for CSAH 9 running south to north on section line. Notes show corner marked by an iron with ties:

16" Maple	NW	49.3'
15" Ash	W	39.0'

Stationing gives distances of 2625.4 feet to the SE corner and 2616.3 feet to the NE corner with a delta angle of 0-16' left.

1963 County Surveyor's Record Book 2, page 436, notes a found hub that was replaced with an iron and the following reference ties.

TP	SW	61.7
10" Birch	NW	62.9
16" Twin Basswood	W	95.45

(Also noted in Notebook No. 234)

2007 Benton County Surveyor's Office found a 3/4" solid pin at the centerline of CSAH 9. The position is 2616.36 feet from the Northeast corner and 2625.17 feet from the Southeast corner of Section 26. Those distances agree very well with the distances in 1932 and 1961. The solid pin was accepted as the obliterated position of the Quarter corner.

County Coordinates
NAD 83 (1996 Adjustment)
N-140620.177
E-568648.025