

**Statement of Evidence:**

**I183**

East Quarter Corner of Section 18, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established this corner and set a wood post and bearing trees were recorded as follows:

22" Maple	S 68 1/2 W	6 links
7" Ironwood	N 45 E	4 links

1915 County Surveyor's Record Book 2, pages 420 and 421, and Record Book A, Map No. 15, contain a survey by J. P. Soderstrum of Section 18. Notes state he found corner marked by an iron pipe set in the intersection of roads by Felix Parent. Made ties: Tele Pole NW 206 links and Tele Pole SE 60 links and Tele Pole NE 76 links. Survey shows corner 40.54 chains north of the southeast corner of Section 18.

1927 County Engineer's Notebook No. 80 for survey of SAR 6 running north to south. Notes show corner in road intersection. Stationing gives distances of 2657.9 feet to the NE corner. Ties:

TP	NE	41.1'
TP	SE	41.5'

1944 County Engineer's Notebook No. 163 contains a road survey for SAR 6 running from south to north on section line. Corner is shown marked by an iron pipe in center of road with town road east and west. Same ties as 1927. Stationing gives distance of 2661.2 feet to the NE corner.

1953 County Engineer's Notebook No. 196 contains a road survey for SAR 6 running from south to north on section line. Corner is shown marked by an iron in center of road with town road east and west. Same ties as 1955 below. Stationing gives distance of 2661.2 feet to the NE corner.

1955 County Surveyor's Records in Book 2 on pages 420 gives ties to an iron:

TP	NE	64.45
PP	NW	48.45
TP	SW	59.3

1979 William Lunser, LS 9394, found no monument and set 1/2" iron pipe from County ties in road intersection.

1988 William Lunser replaced iron pipe with cast iron monument and filed Certificate of Location (No. 419267). He gives distances of 2674.39 feet to SE corner of Section 18. (Compares well with Soderstrum's 40.54 chains = 2675.64 feet), 2662.72 feet to the NE corner, and 4940.07 feet to the West 1/4 corner.

2008 The County Surveyor's Office searched and found a cast iron monument 0.3' under the intersections of east-west (90<sup>th</sup> St. NE) and north-south (County Road No. 6) roads. Old ties were not recovered. Distances to the NE Cor. and SE Cor. measured as 2662.68 ft (40.34 ch.) and 2674.47 ft. (40.52 ch.), respectively, which agree with Soderstrum's 1915 measurements, and measurements by the County Highway in 1944 and 1955. The Surveyor accepts the position as the best evidence, and updated ties.

County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-151144.714  
E-547353.700