

**Statement of Evidence:**

**I163**

East Quarter Corner of Section 16, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Blk Ash	S 74 1/2 E	14 links
12" Linden	S 37 W	19 links

1923 County Engineer's notebook No. 33 is for road survey of SR No. 7 running north from this corner. Gives distance of 2667.4 feet to the NE corner. Ties:

NE Cor Found. Brown House	SE	126.5'
Cor. F.P.	SW	44.8'

1925 County Surveyor's Record Book 2, page 416, and County Engineer's notebook 45 notes the following reference ties:

TP	SE	42.5
R Oak	NW	32

Corner is 2665.3 feet north of the SE corner.

1951 Roll B-12, of the MN/DOT Highway plans for S.P.0504 (TH23=23), dated November 9, 1951, note the corner is at the centerline of a road north/south/east/west. It also notes the following distances:

2667.8 feet to the SE Cor Sec 16
587.2 feet south to centerline

1988 Information from Paul Wollen's field book 53 on page 83 shows Bruce Skipton, LS 17768, dug corner area with a backhoe and found a pointed stone with wood pieces around it and set a cast iron monument above the found stone. Reference ties:

PK in PP	NW	74.03
PK in PP	SW	47.57

Doc. No. 191330 for the Northeast corner of Section 16 notes the following distances:

2667.40 feet to the NE Cor 16
5366.66 feet to the W 1/4 Cor 16
2664.97 feet to the SE Cor 16

2003 Westwood Professional Services, Inc. found a CIM at the intersection of the centerlines of County Road 7 and 95<sup>th</sup> Street NE. Distances to section corners north and south checked well with 1988 distances. We measured south 584.12 feet to the centerline of TH 23.

County Coordinates by GPS to CIM

NAD 83 (1996 Adjustment)

N- 150917.169

E- 557920.032