

**Statement of Evidence:**

**I153**

East Quarter Corner of Section 15, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 US General Land Office survey established this corner and set a wood post and bearing trees were recorded as follows:

8" Elm	N 11 E	75 links
5" Elm	N 60 W	77 links

1951 Roll B-12, of the MN/DOT Highway plans for S.P.0504 (TH23=23), shows the corner assumed at the intersection of roads east/south/west and a fence line north. It notes a distance of 2264.8 feet north to the centerline.

1994 David Regan, LS 12236, placed an iron monument at the intersection of roads South and East-West and fence line north. A Certificate of Location (#231239) was filed.

2001 Westwood Professional Services, Inc. found a 1/2" iron monument capped RLS #12236 at the intersection of the centerlines of 90<sup>th</sup> Street NE running east and west and 175<sup>th</sup> Avenue NE running south. Removed and set cast iron monument and established reference ties.  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 150980.627  
E- 563176.249

2008 The County Surveyor's Office searched and found Westwood's 2001 cast iron monument approximately 0.3' below the surface at the intersection of an east-west gravel road (90<sup>th</sup> Street N.E.) and a south gravel road (175<sup>th</sup> Avenue N.E.). A tie to the travelled centerline of State Highway 23, measured 2262 ft.  $\pm$ , which agrees with 1951 measurements. Position agrees with Regan's ties and occupation and is accepted as marking the best evidence and updated ties. Coordinates to same obtained by GPS agree with those reported in 2001 above.