

**Statement of Evidence:**

East Quarter Corner of Section 13, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office surveyor, Theodore Conkey, set a wood post at this location and bearing trees were recorded.

8" Maple	S 16 W	49 links
10" Basswood	N 38 E	39 links

Line trees were noted as a 10" Basswood South 19.51 chains and a 30" Pine North 23.15 chains.

1995 John Oliver, LS 8194, Mille Lacs County Surveyor, set corner lost and filed Certificate of Location (No. 244626). Corner falls in center of north-south road. (See cert for details.) Corner monument set was a 3/4 " iron pipe. Note: Distances from John Oliver & Associates give 2634.89 feet to the section corners.

County Coordinates from John Oliver & Associates traverse  
NAD 83 (1986 Adjustment)  
N- 151283.375  
E- 573688.281

2002 No resurvey information was found on this corner in the Benton County records.

2003 Survey & Engineering Professionals, Inc. (Linda Brown, LS 23682) found iron pipe and coordinates determined from their traverse information.

County Coordinates by Traverse (SEPI)  
NAD 83 (1996 Adjustment)  
N- 151283.445  
E- 573687.888

2008 The County Surveyor's Office searched and found a 3/4" iron pipe approximately 0.4' below the surface of the centerline of the north-south gravel road (195<sup>th</sup> Avenue N.E.). Position distance to the SE Cor. gives 2634.52 feet which agrees well with 1995 distance of 2634.89 feet reported by Oliver. Surveyor accepts the position as the best evidence and updated ties.

County Coordinates by GPS to 3/4" iron pipe  
NAD 83 (1996 Adjustment)  
N- 151283.286  
E- 573688.243