

Statement of Evidence:

I083

East Quarter Corner of Section 8, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

9" Sugar	S 29 E	8 links
10" Sugar	N 56 1/2 W	30 links

1892 Road Survey Report by Felix Parent, County Surveyor, shows survey terminating at this corner from the west along the quarter line with a distance of 79.06 chains to the East 1/4 corner of Sec. 7.

1938 County Engineers' Notebook No. 119 shows survey of CAR 27 running from north to south. Notes show approximate corner being in intersection of town road west and fence line east. Stationing gives distances of 2699.3 feet to the NE corner and 2661.5 feet to the SE corner.

2008 The County Surveyor's Office searched and found a 1/2" iron pipe below centerline intersections of a north-south road (155th Ave. NE) and a road to the west (100th St. NE). Comparing distances to the NE Cor. and the SE Cor. gives agreeable results with those reported in 1938 (2694.38 ft. & 2664.65 ft., respectively). Comparing the distance to the E 1/4 Cor. of Sec. 7 gives 5202.38 ft. (78.82 ch.) which agrees with Parent's distance in 1892 of 79.06 ch. The position fits an old occupation line to the east and is accepted as the best evidence. Ties were made.

County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N-156462.439
E-547349.224