

Statement of Evidence:

I013

The East Quarter Corner of Section 1, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office surveyor, Theodore Conkey, set a wood post at this location and bearing trees were recorded.
- | | | |
|------------|--------|----------|
| 20" W. Oak | N 81 W | 24 links |
| 6" Bass | S 83 E | 11 links |
- Line trees were noted as an 8" W Oak South 19.82 chains and an 18" Elm North 13.24 chains.
- Undated County Surveyor's Record Book 1, page 386, shows the following B.T.
- | | | |
|-------------|-----------|-----------|
| 12" W. Pine | N 6 1/2 E | 209 links |
|-------------|-----------|-----------|
- 1902? County Surveyor's Record Book A, Map No. 33, shows a survey of Section 1 by John Whilt notes a distance of 39.46 1/4 chains to the NE and 39.69 3/4 chains to the SE Corner.
- 1902? County Surveyor's Record Book 2, page 386, and Record Book A, Map No. 43, shows a second survey of Section 1 by John Whilt. A distance of 37.67 1/2 chains (2486.55 feet) to the NE corner and 40.07 1/2 chains (2644.95 feet) to the SE corner.
- 1916 Mille Lacs County Surveyor's Record Book B, pages 16-19, shows a survey of Section 6, 37-27 by S. L. Kennedy. He notes "probable gov't corner marked by a square sandstone with +, 2 feet in length. New ties:
- | | | |
|-------------|--------|--------|
| 14" Elm | S 25 W | 38.94' |
| 12" W. Pine | N 9 E | 24.4' |
- Measured 2652.8 feet to the SW corner and 2495.15 feet to the NW corner of Section 6. 1/16th corners were set north and south.
- 1994 John Oliver, LS and Mille Lacs County Surveyor, found a red square sandstone monument with an "X" and established reference ties. A Certificate of Location (#244622) was recorded. Note: Distances from John Oliver & Associates are 2494.78 feet to the NE corner and 2652.42 feet to the SE corner.
County Coordinates from traverse information:
NAD 83 (1986 Adjustment)
N- 161839.187
E- 573524.912
- 2001 Westwood Professional Services, Inc. found a red square sandstone with an "X" and established reference ties.
County Coordinates Obtained by GPS:
NAD 83 (1996 Adjustment)
N- 161839.546
E- 573524.897