

Statement of Evidence:

1362

Northeast Corner of Section 36, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Elm	S 14 E	20 links
8" Blk Ash	N 79 E	10 links
10" Blk Ash	N 58 W	37 links
8" Basswood	S 68 W	16 links

Line trees were noted as a 8" Elm South 17.23 chains and a 14" W Oak North 21.78 chains.

Undated Reference ties to an iron

24" Twin Oak	NE	125.7
16" R Oak	SW	96.0
18" Elm	SW	127.6

Unspecific reference ties exist

1902 County Surveyor's Record Book A, Map No. 30, contains a survey of Section 25 by John Whilt.

1909 Mille Lacs County Surveyor's Record Book B, pages 196 & 197, S. L. Kennedy notes in 1916 that R.S. Chapman established corner found Gov't Ash stumps standing NE and NW with distances good and bearings approximate. Supported with area witnesses. Kennedy notes good gov't corner in road marked by an iron and stake with the following reference ties

13" W Oak	N 68-30 E	76.66 feet
15" W Oak	S 50-20W	118.0 feet
18" Twin Oak	N 23-45 E	125.3 feet

1926 County Engineer's Notebook No. 49 contains survey for CR 4 running west to east. Notes show corner marked by an iron in road intersection with ties:

Cor FP	SE	42.6
Cor FP	SW	36.7

1940's County Engineer's Notebook No. 160 contains road survey for SAR No. 4 running west to east along the section line. Corner is shown as a 2"wood hub and iron in center of 4-way road intersection. Ties:

24" Double W. Oak	NE	125.2'
18" Elm	SW	127.6'
16" R. Oak	SW	96.0'

1947 Mille lacs County Highway Department notes list ties re-rod:

PP	NW	53.4
Iron Pin Cem. Cor. Stake	SE	46.6
Guy P	SW	55.7

1971 County Surveyor's Record Book 2, page 456, notes iron and wood with the following ties:

Benton County Surveyor's Office
Jason W. Oberg, Deputy County Surveyor
Minnesota License No. 45872
Page 2 of 2

PP	NW	55.33
Guy Pole	SW	55.5
Iron (Cemetery Corner)	SE	46.0

(Same ties in Notebook No. 160.)

1988 John Oliver, LS 8194, found a rebar in the centerline of a north/south and east west road.

1990 John Oliver replaced said found rebar with a cast iron monument and filed a Certificate of Location (#244631).

1993 Sidney Williamson, LS 10918, found a $\frac{1}{2}$ " open and replaced it with a cast iron monument and filed a Certificate of Location (#227419).

2004 County Coordinates obtained by GPS to CIM
NAD 83 (1996 Adjustment)
N- 138100.625
E- 573961.500
Note: Coordinates agree well with John Oliver & Associates coordinates from traverse information.

2008 The County Surveyor's Office searched and found the location of a cast iron monument at the intersection of the centerlines of east-west bituminous road (65th Street N.E.) and north-south gravel road (195th Avenue N.E.). Position gives distances to E $\frac{1}{4}$ corner of Section 25 and the E $\frac{1}{4}$ corner of Section 36 as 2640.49 feet and 2640.53 feet respectively, which agree with Oliver's 1996 reported distances of 2640.36 feet. Surveyor accepts the position as the best evidence and set a PK nail with a Benton County Surveyor disk and updated ties.

County Coordinates to PK obtained by GPS
NAD 83 (1996 Adjustment)
N- 138100.662
E- 573961.581