

**Statement of Evidence:**

**1352**

Northeast Corner of Section 35, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

30" Blk Ash	N 38 1/2 W	50 links
14" Linden	S 35 W	19 links

Undated County Surveyor's Record Book 2, page 434 notes the following B.T.  
10" Elm N 38 E 69 links

1901 County Surveyor's Record Book A, Map No. 35, shows a survey of Section 35, 37-28 by John E. Whilt.

1902 County Surveyor's Record Book A, Map No. 30, shows a survey of Section 25 by John Whilt and Map No. 32 shows a survey of Section 26 by John Whilt.

1926 County Engineer's notebook No. 49 contains survey for CR 4 running west to east. Notes show corner marked by an iron pipe in road intersection with ties:

FP	SE	29.3'
TP	SW	44.8'

Same ties listed in County Surveyor's Record Book 2, page 454.

1930 County Engineer's notebook No. 58 shows road survey by H. G. Elletson starting at this corner and running south. Corner is shown as an iron pipe in center of road east-west with ties to wood stake:

12" Bass.	SE	224.8'
8" Ash	SE	205.7'

1932 County Engineer's Notebook No. 80 for survey of SAR 9 running north from this corner.

1940's County Engineer's Notebook No. 160 contains road survey for SAR No. 4 running west to east along the section line. Corner is shown as a wood stake in center of 4-way road intersection. Ties:

12" Bass.	SE	224.8'
8" Ash	SE	205.7'

1961 County Engineer's Notebook No. 234 contains survey for CSAH 9 running south to north on section line. Notes show nail in center of CSAH 4. Ties:

TP	SE	71.1'
TP	SW	61.2'

1971 County Surveyor's Record Book 2, page 456, notes a nail over a stake and ties:

Cor FP	SW	61.4
PP	NE	61.85
Tele Ped	NW	58.3

(Also noted in Notebook No. 160.)

1983 David Regan, LS 12236, found a 1" Iron Pipe in the centerline of roads north/south and east/west. He filed a Certificate of Location (#167979), which shows fitting two 1971 ties.

1993 Sidney Williamson, LS 10918, found a 1/2" open iron pipe and replaced it with a cast iron monument. He filed a Certificate of Location (#227417).

2004 County Coordinates obtained by GPS to PK Nail:

NAD 83 (1996 Adjustment)  
N- 137995.090  
E- 568626.882

2007 Benton County Surveyor's Office found a PK Nail at the centerline-centerline of CSAH 4 and CSAH 9. The coordinates for the PK nail are the same as the coordinates of the PK nail found in 2004. This position agrees with the position filed by Regan in 1983 so it is accepted as the Obliterated Section corner.