

Statement of Evidence:

The Northeast Corner of Section 34, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

14" Elm	N 79 E	24 links
16" Elm	S 76 W	20 links

A line tree was noted as a 20" Elm South 0.89 chains.

1901 County Surveyor's Record Book A, Map No. 35 shows a survey of Section 35, 37-28 by John E. Whilt.

1902 County Surveyor's Record Book A, Map No. 32 shows a survey of Section 26 by John Whilt and Map No. 38 shows a survey of Section 27 by John Whilt. Corner is noted as being marked by an iron pin.

No Date (Old) County Surveyor's Record Book 2, page 436 lists ties:

8" W. Oak	S 44 W	72 links
6" W. Oak	N 55 1/4 W	65 1/2 links
4" W. Oak	S 47 1/2 E	78 links

1926 County Engineer's notebook No. 49 contains survey for CR 4 running west to east. Notes show corner marked by an iron pin in road intersection with ties:

6" Birch	NE	55.0'
8" Oak	SE	60.0'

1940's County Engineer's Notebook No. 160 contains road survey for SAR No. 4 running west to east along the section line. Corner is shown as a wood plug and iron pipe in center of road with town road north and south. Ties:

12" W. Oak	NW	125.8'
12" Box Elder	NE	126.3'

1971 County Surveyor's Record Book 2, page 452 lists same ties as shown on Regan's certificate in 1983 and Notebooks 49 and 160. Notation in Notebook 160 shows found corner and placed iron over with ties:

PP	SE	56.4'
PP	SW	128.2'
T. Ped.	NW	49.7'

1983 Certificate of Location (Doc. No. 167981) filed by David Regan, LS 12236, shows he found a 1 1/4" iron rod in center of road intersection.

1993 Certificate of Location (Doc. No. 227421) filed by Sidney Williamson, LS 10918, shows he found the same 1 1/4 " solid iron rod and replace it with a cast iron monument.

2003 County Coordinates computed from traverse information furnished by Surveying & Engineering Professionals, Inc.
NAD 83 (1996 Adjustment)
N- 137865.716
E- 563324.103

2007 Benton County Surveyor's Office found a PK nail at the centerline/centerline intersection of CSAH 4 and 175th Ave. NE. The coordinates of the PK nail match the coordinates of 2003 so the PK nail was accepted as the Obliterated Section corner.