

Statement of Evidence:

Northeast Corner of Section 27, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Elm	N 3 E	13 links
10" Blk Ash	S 16 1/2 E	13 links

1902 County Surveyor's Record Book A, Map No. 32 shows a survey of Section 26 by John Whilt and Map No. 38 shows a survey of Section 27 by John Whilt. Corner is shown as a post.

1915 County Surveyor's Record Book 2, pages 430 and 431, and Record Book A, Map No. 3, shows a survey of Section 23 by J. P. Soderstrum. Notes show he set a stone for the corner 6" below road surface in intersection of roads from old Elm BT stump. Corner was 6 feet south of a culvert.

1927 H. G. Elletson adds note to above record that old corners found along the south line of Section 23. (Engineer's Notebook 48)

1929 County Engineer's notebook No. 58 shows road survey by H. G. Elletson running west to east. Corner is shown as a stake with ties:

County Surveyor's Record Book 2, pages 438 give reference ties to hub:

TP	NW	38.75
TP	SW	83.1

County Engineer's records show reference ties to hub:

TP	NW	39.0
TP	SW	80.2

NOTE: Corner needs excavation for stone.

County Coordinates
NAD 83 (1996 Adjustment)
N-
E-