

Statement of Evidence:

I252

Northeast Corner of Section 25, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Blk Ash	S 76 W	82 links
12" Blk Ash	N 75 W	80 links
12" Blk Ash	N 82 E	58 links
12" Blk Ash	N 72 E	50 links

1902 County Surveyor's Record Book 2, pages 432 and 434, and Record Book A, Map No. 30, shows a survey of Section 25 by John Whilt. Ties:

10" Elm	N 66 3/4 E	199 links
10 W. Elm	N 60 3/4 E	197 links

1929 County Engineer's Notebook No. 58 shows a road survey by H. G. Elletson running west to east. Corner is shown as hub set in center of road with ties:

FP	NE	27.7
FP	SE	36.3

1996 John Oliver, LS 8194, Mille Lacs County Surveyor, set 3/4 " iron pipe in intersection of north-south road east-west road and filed Certificate of Location (No. 244629).

2004 County Coordinates obtained by GPS to 3/4 " iron pipe

NAD 83 (1996 Adjustment)

N- 143380.592

E- 573854.880

Note: Coordinates check with information from John Oliver & Associates.

2008 The County Surveyor's Office searched and found a 3/4" iron pipe approximately 0.3' below the surface at the intersection of an east-west gravel road (75th Street N.E.) and north-south gravel road (195th Avenue N.E.). Position gives a distance to the E 1/4 Cor. as 2640.48 feet which agrees with the same distance reported by Oliver in 1996. Surveyor accepts the position as the best evidence and updated ties. Coordinates from 2004 were verified.