

**Statement of Evidence:**

**I202**

Northeast Corner of Section 20, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Aspen	N 1 W	225 links
7" Bur Oak	S 89 W	160 links

1938 County Engineers' Notebook No. 119 shows survey of CAR 27 running from north to south. Notes show corner being a set spike in center of road on east and west fence lines. Ties:

FP	W	35.1'
FP	NE	44.6'

Stationing gives distances of 2679.1 feet to the East 1/4 corner Section 17 and 2633.7 feet to the East 1/4 corner Section 20 with a delta angle of 0-28' left.

1951 MN/DOT alignment map for TH 23 shows corner assumed at center of north-south road and fence lines east-west. Distances shown:

964.2'	south to centerline
1702.6'	east to centerline
2634.1'	to East 1/4 corner Sec. 20

2001 William Lunser, LS 9394, set a 1/2 " iron pipe in center of north-south road and in line with fence east and filed Certificate of Location (No. 283116). Gives distances of:

2682.20'	to East 1/4 corner Sec. 17
2615.15'	to North 1/4 corner Sec. 20
2630.39'	to East 1/4 corner Sec. 20

2011 The County Surveyor's Office found a 3/4 inch iron pipe in the centerline of the North-South road with a distance of 2630.33 feet to the East Quarter corner, 2615.14 feet to the North Quarter corner and 2682.21 feet to the East Quarter corner of Section 17. The 3/4 inch iron pipe is accepted as marking the obliterated corner position based on the 1938 corner referenced in the County Engineers' Notebook No. 119.

County Coordinates  
NAD 83 (1996 Adjustment)  
N- 148349.607  
E- 552580.195