

**Statement of Evidence:**

Northeast Corner of Section 19, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established this corner and set a wood post and bearing trees were recorded as follows:

22" W Oak	N 44 1/2 W	39 links
24" W Oak	N 32 E	17 links

1915 County Surveyor's Record Book 2, pages 420 and 421, and Record Book A, Map No. 15, contain a survey by J. P. Soderstrum of Section 18. Notes he found an iron stake set by Felix Parent in intersection of roads.

1937 County Highway ties to hub in Book 2, page 418:

TP	SE	38.5
FP	SW	38.8

1951 MN/DOT alignment map for TH 23 shows corner assumed in center of road.

1979 County Highway ties note a spike set at corner in center north-south road and fence line east. Book 2, page 422, shows an iron at the corner.

1988 William Lunser, LS 9394, found 1979 spike and replaced with a cast iron monument. Filed Certificate of Location (No. 191270). Gives distances of 2674.39 feet to the East 1/4 corner of Section 18 and 2640.69 feet to the North 1/4 corner of Section 19.

County Coordinates  
NAD 83 (1996 Adjustment)  
N-  
E-