

Statement of Evidence:

I152

Northeast Corner of Section 15, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established this corner and set a wood post for the corner and bearing trees were recorded.

16" Tamarack	N 12 1/2 E	217 links
20" Tamarack	S 5 1/2 W	235 links

1902 County Surveyor's Record Book 2, page 406 and Record Book A, Map No. 31 contains a survey by John E. Whilt of Section 11.

1951 Roll B-12, of the MN/DOT Highway plans for S.P.0504 (TH23=23), dated November 9, 1951, note the corner is at intersection of fence line north/south/west. It also notes stationing and angles with the following distances:
819.2 ft east to centerline
426.6 ft south to centerline

2000 Westwood Professional Services, Inc. computed corner at lost position.

2003 Westwood Professional Services, Inc. searched corner area based on MN/DOT information and found remains of down fence lines west and north. No evidence of a corner monument was found. On 3/7/03 set a 1/2 " iron pipe at apparent fence intersection. Following distances were computed to centerline of TH 23 along section lines, which varies slightly from MN/DOT stationing:
822.61 feet east
427.63 feet south
This position is 15 feet southwest of the corner position computed in 2000.
County Coordinates by sidetie:
NAD 83 (1996 Adjustment)
N- 153670.026
E- 563190.073