

Statement of Evidence:

I142

Northeast Corner of Section 14, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established this corner and set a wood post and bearing trees were recorded as follows:

9" Tamarack	S 60 W	30 links
9" Tamarack	N 6 W	18 links

1902 County Surveyor's Record Book 2, page 406, and Record Book A, Map No. 31 contains a survey by John E. Whilt of Section 11.

1951 Roll B-12, of the MN/DOT Highway plans for S.P.0504 (TH23=23), dated November 9, 1951, show the corner at the intersection of roads north/south/east and a distance of 2292.1 feet north to the centerline.

1961 County Engineer's Notebook No. 234 contains survey for CSAH 9 running south to north on section line. Notes show corner with same ties as shown below in 1963.

1963 County Surveyor's Record Book 2, page 412, shows an iron with the following reference ties:

P.P.	SW	148.45
P.P.	SE	113.3

Undated ties.

North end culvert	NE	47.0
P.P.	SE	13.15

2001 On October 15, 2001 Westwood Professional Services, Inc. found 1" x 24" solid iron pin at the intersection of the centerlines of County Road 9 (running north and south) and 95th Street NE (running east). Removed the 1" solid iron pin and set a cast iron monument at the location and established reference ties.

2003 Corner was found to be 2290.46 feet south of the centerline of TH 23.
County Coordinates obtained by GPS to CIM
NAD 83 (1996 Adjustment)
N- 153837.941
E- 568455.583