

Statement of Evidence:

Northeast Corner of Section 12, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

20" W Oak	N 35 E	2 links
30" Pine	N 54 W	61 links
8" W Ash	S 63 W	22 links
12" Elm	S 42 1/2 E	23 links

1902? County Surveyor's Records Book 2, page 386, and Record Book A, Map Nos. 33 and 43, show two surveys of Section 1 by John Whilt.

1916 Mille Lacs County Surveyor's Record Book B, pages 16-19, shows a survey of Section 6, 37-27 by S. L. Kennedy. He notes "gov't corner marked by a sleigh shoe and 4 small rocks. Corner was witnessed by Andrew Kennedy and Mrs. Swanson. Corner is in west 1/2 of road with remains of 2 gov't BT's NE and NW. New ties:

6" W. Oak	N 38 W	59.4'
4" W. Oak	S 22-30 E	58'

Measured 540.5 feet south to the center of RR track.

1951 Roll B-12, of the MN/DOT Highway plans for S.P.0504 (TH23=23), dated November 9, 1951, note the corner 405.5 feet north of new centerline.

1994 John Oliver found 1/2" x 1/2" x 1 1/2" sleigh shoe and replaced with a CIM and filed Certificate of Location (No. 244623). Certificate shows corner 405.38 feet north of the center of TH 23.

County Coordinates from John Oliver & Associates traverse:

NAD 83 (1986 Adjustment)
N- 153917.998
E- 573650.578

2007 The Benton County Surveyor's Office located the CIM set by Oliver in 1994. The CIM is accepted as marking the obliterated corner position. Coordinates were obtained and reference ties established.

County Coordinates obtained by GPS:
NAD 83 (1996 Adjustment)
N-159187.641
E-573574.837