

**Statement of Evidence:**

**I361**

North Quarter Corner of Section 36, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" W Oak	S 30 E	24 links
10" Linden	N 43 1/2 E	23 links

1902 County Surveyor's Record Book A, Map No. 30 is a survey of Section 25 by John Whilt which shows a distance of 40.43 1/2 chains (2668.71 feet) to the NE corner Sec 36 and a distance of 39.97 1/2 chains (2638.35 feet) to the NW corner Sec 36.

1926 County Engineer's notebook No. 49 contains survey for CR 4 running west to east. Notes show corner marked by a found wooden plug in line with road south. Ties (Also listed in County Surveyor's Record Book 2, page 456):

TP	SE	54.1
Cor FP	SW	29.0

Stationing gives distances of 2652.7 feet to the NW corner and 2682.7 feet to the NE corner with a delta angle of 2-06' left.

1940's County Engineer's Notebook No. 160 contains road survey for SAR No. 4 running west to east along the section line. Corner is shown as a wood hub in center of road with fence north and town road south. Ties:

16" Maple	SE	76.2'
12" Maple	SE	112.5'

Stationing gives distances of 2652.7 feet to the NW corner and 2683.7 feet to the NE with a delta angle of 2-06' left. County Surveyor's Record Book 2, page 456, notes the same ties.

1993 Sidney Williamson, LS, found a 1/2" solid iron at the centerline of roads east/west/south. He replaced it with a cast iron monument and filed a Certificate of Location (#227418). He measured 2652.39 feet to the NW corner and 2684.37 feet to the NE corner of Section 36.

Note: The iron found in 1993 fits within one foot of the proportion to the 1902 position and fits reasonably with the highway information.

2004 Found PK Nail at apparent corner and measured 2652.26 feet to the NW corner and 2684.28 feet to the NE corner with a deflection angle of 2-05'-24".  
County Coordinates obtained by GPS to PK Nail:  
NAD 83 (1996 Adjustment)  
N- 137998.889  
E- 571279.144

2008 The County Surveyor's Office searched and found the PK Nail as referenced in 2004, above. Position measures 2652.32 feet (40.19 ch.) to the NW corner and 2684.23 feet (40.67 ch.) to the NE corner with a deflection angle of 2-05'-41". Said measurements agree well with 1940's County Engineer's measurements. Position is accepted as the best evidence and ties were updated.

County Coordinates obtained by GPS to PK Nail:  
NAD 83 (1996 Adjustment)  
N- 137998.779  
E- 571279.199