

**Statement of Evidence:**

North Quarter Corner of Section 35, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Tamarack	S 40 W	8 links
10" Tamarack	N 49 W	8 links

1901 County Surveyor's Record Book 2, pages 436 and 454 and Record Book A, Map No. 35, shows a survey of Section 35, 37-28 by John E. Whilt. The corner is shown set lost, midway between section corners, with a distance of 80.05 chains for the mile. Ties:

5" Poplar	SE	29.8
TP	S	30.7

1902 County Surveyor's Record Book A, Map No. 32, shows a survey of Section 26 by John Whilt. The corner is shown midway between section corners with a distance of 80.06 chains for the mile.

1926 County Engineer's notebook No. 49 contains survey for CR 4 running west to east. Notes show corner marked by a wooden plug 2.6 feet right of POT with fences north and south. Ties:

Cor. F. P.	North	30.8'
5" Pop.	SE	29.8'

Stationing gives distances of 2652.5 feet to the NW corner and 2649.1 feet to the NE corner.

1940's County Engineer's Notebook No. 160 contains road survey for SAR No. 4 running west to east along the section line. Corner is shown 2.6 feet right of POT with fence lines north and south. Ties to POT:

3 <sup>rd</sup> FP	S	50.8'
5" Pop.	SW	69.3'

Stationing gives distances of 2652.8 feet to the NW corner and 2650.2 feet to the NE corner to the POT.

1983 David Regan, LS 12236, found a capped ½ " iron pipe in center of east-west road and in line with fence south. He filed Certificate of Location (167980). Ties on Certificate are also listed in County Highway notes to a ¾ " iron monument.

1993 Sidney Williamson, LS 10918, found ½ " iron pipe and replaced it with a cast iron monument. He filed Certificate of Location (227420). Distances given:

2656.24 feet to NW corner
2648.04 feet to NE corner

Distances show corner is 4.1 feet east of the lost position.

County Coordinates  
NAD 83 (1996 Adjustment)  
N-  
E-