

Statement of Evidence:

I301

North Quarter Corner of Section 30, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

6" Blk Ash	S 57 W	42 links
9" Tamarack	N 9 E	22 links

1951 MN/DOT alignment map for TH 23 shows corner assumed at intersection of fences west and south being 72.9 feet north of centerline.

2001 Sam Deleo, LS 40431, reestablished corner based on MN/DOT information from TH 23 and fence lines south and west. No resurvey information was found on this corner in the Benton County records.

2002 Sam Deleo set cast iron monument.

2003 Certificate of Location filed by Sam Deleo (Doc. No. 298887)

2008 The County Surveyor's Office searched and found Deleo's monument (1/2" iron pipe with cap "40341") 0.2' ft above the surface at 65 ft.± northwesterly (as measured perpendicular) of the centerline of State Highway 23. Position agrees with a field line to the west and the same shown on MnDOT Right-of-Way Map No. 12-57. Distance to the NW Cor. gives 2372.80 ft. (35.95 ch.) which agrees reasonably with GLO distance to same as 2382.6 ft. (36.10 ch.). Position is accepted as the best evidence and ties were updated.

County Coordinates obtained via GPS
NAD 83 (1996 Adjustment)
N-143136.444
E-544774.785