

Statement of Evidence:

I281

North Quarter Corner of Section 28, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

- 1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

20" Elm	S 15 W	7 links
16" Bur Oak	N 14 E	5 links

- 1929 County Engineer's notebook No. 58 shows road survey by H. G. Elletson running west to east. Corner is shown in line with fences north and south with ties:

Cor. F.P.	N	31.7'
Cor. F.P.	S	29.1'

Stationing gives distances of 2663 feet to the NW corner and 2651.8 feet to the NE corner with a delta angle of 0-22' left.

County Surveyor's Record Book 2, page 440, lists same ties.

- 2008 On 7-10-07 the County Surveyor's Office excavated an area 10' x 10' x 5' deep at the centerline of an east-west gravel road (County Road No. 52) and on line with a north fence line and a south fence line. At approximately 4.5' below ground a charred tamarack wood post was found. Surveyor accepts the post as being the Corner post as set in 1855. A cast iron monument was set as marking the location of the found post and ties were taken to same.

County Coordinates
NAD 83 (1996 Adjustment)
N-143035.409
E-555390.352