

**Statement of Evidence:**

**I201**

North Quarter Corner of Section 20, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Sugar	N 50 1/2 E	29 links
12" Sugar	S 52 E	32 links

1951 MN/DOT alignment map for TH 23 shows corner assumed at intersection of fence lines east, west, and north.

2001 William Lunser, LS 9394, found a 1/2" iron pipe with cap No. 12236 (Dave Regan) at the intersection of fence lines north, east, and west. He filed Certificate of Location (No. 283122). Gives measurements of 2618.34 feet to the NW corner and 2615.15 feet to the NE corner.

2002 No resurvey information was found on this corner in the Benton County records.

2008 The County Surveyor's Office searched and found a 1/2" iron pipe with cap #12236 at an east-west and north fenceline intersection, as reported by Lunser in 2001. Distances to the NW and NE Corners measures 2618.42 ft. and 2615.14 ft., respectively. The Surveyor accepts the position and updated ties.

County Coordinates obtained by GPS

NAD 83 (1996 Adjustment)

N-148439.161

E-549966.585