

Statement of Evidence:

I151

North Quarter Corner of Section 15, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 US General Land Office survey established this corner and set a wood post and bearing trees were recorded as follows:

10" Elm	N 44 1/2 W	5 links
5" B. Ash	S 17 1/2 W	19 links

1951 Roll B-12, of the MN/DOT Highway plans for S.P.0504 (TH23=23), shows an oak hub at the intersection of roads north/south and a fence line east/west. The map shows a distance of 1821.0 feet south to the new centerline of the TH 23.

1994 David Regan, LS 12236, placed an iron monument in centerline of north south gravel road and on tree line east (taken from Trunk Highway 23 information). He filed a Certificate of Location (#231240).

2001 Westwood Professional Services, Inc. found a 1/2" open at the intersection of the centerlines of 170th Avenue NE (running north and south) and a tree line (from the south). Removed and set cast iron monument and established reference ties.

2003 Westwood Professional Services, Inc. found the CIM to be 1812.14 feet north of the centerline of TH 23.
County Coordinates by GPS to CIM
NAD 83 (1996 Adjustment)
N- 153600.465
E- 560540.945

2008 The County Surveyor's Office searched and found a cast iron monument approximately 0.8' below the surface of a north-south gravel road (170th Avenue N.E.) and on line with a west fence line and an east tree line. Surveyor accepts cast iron monument as marking the best evidence and updated ties. Coordinates to same obtained by GPS agree with those reported in 2003 above.