

Statement of Evidence:

I121

North Quarter Corner of Section 12, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Lind	N 43 W	35 links
8" Blk Ash	S 39 E	31 links

1902? County Surveyor's Record Book A, Map No. 33, shows a survey of Section 1 by John Whilt, which notes a distance 77.86 chains between section corners.

1902? County Surveyor's Record Book 2, page 386, and Record Book A, Map No. 43, shows a second survey of Section 1 by John Whilt. Survey gives a distance of 39.46 ½ chains (2604.69 feet) to the SW corner of Section 1 and a distance of 39.15 chains (2583.90 feet) to the SE corner Section 1. (78.615 chains for the mile = 5188.59 feet)

1951 MN/DOT alignment map for TH 23 shows corner assumed at fence line intersection north, south, and west with corner 1629.1 feet north of centerline.

2007 Westwood found a spike at a fence intersection. The overall north line of Section 12 (5204.42 feet) fits the 1902 Map No. 43 distance (5188.59 feet) within in about 16 feet. The half mile splits to the found spike 2611.64 feet to the west and 2592.86 feet to the east fit proportionally within one foot. I accepted the spike as marking the obliterated position.

2009 Benton County Surveyor's Office set a ½ inch by 18 inch iron pipe cap No. 19552 in place of spike found in 2007 by Westwood
County Coordinates
NAD 83 (1996 Adjustment)
N-159186.187
E-570981.979