

**Statement of Evidence:**

North Quarter Corner of Section 7, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

7" Ironwood	S 11 E	20 links
8" Elm	N 12 E	20 links

No Date County Surveyor's Record Book 2, page 396, shows the following B.T.  
8" Burr Oak N 36 1/2 E 64 links

1995 William Lunser, LS 9394, found a 1/2" iron pipe of unknown origin that coincides with lines of occupation consisting of fence lines north and south and a township road east and west. Reference ties were established. A Certificate of Location (#234178) was filed. Gives distances of 2627.28 feet to the NE corner and 2234.01 feet to the NW corner.

2001 Westwood Professional Services, Inc. found a 1/2" iron pipe at the intersection of the centerline of 105<sup>th</sup> Street NE (running east and west) and fence lines (running north and south). Found no evidence of the Bur Oak tie tree listed in the County notes. Pipe found fit ties shown on Lunser's certificate. Accepted the pipe as marking the obliterated corner position. Removed the 1/2" pipe and placed a cast iron monument at the location and noted ties. A Certificate of Location (#291186) was filed.

2009 The Benton County Surveyor's Office found a CIM that fits the ties as shown on Certificate of Location #291186. The CIM is 2234.21 feet from the northwest corner and 2627.50 feet from the northeast corner.

County Coordinates obtained by GPS (CIM)

NAD 83 (1996 Adjustment)

N-159139.259

E-544716.205