

Statement of Evidence:

North Quarter Corner of Section 5, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

4" Maple	N 26 E	38 links
4" Elm	S 44 W	24 links

1912 County Engineer's Notebook 2, pages 61, is a road survey for SR No. 2 by M. J. Cleveland. Survey was run on section line east-west. Notes show corner in center of road. Stationing gives distances of 2593 feet to the NW corner and 2607 feet to the NE corner of Section 5.

1915 County Surveyor's Record Book 2, page 394, notes that J.P. Soderstrum found no evidence of the corner, so he set a stake for the corner on line and equal distant from the section corners measuring 78.75 chains (5197.5 feet) for the mile.

1921 County Engineers' Notebook No. 39 shows survey of road on town line with no mention made of this corner. Stationing gives distance of 5205.6 feet between section corners.

1955 County Engineer's Notebook No. 202 shows a survey of SAR 5 running west to east on town line. Corner is shown marked by a spike set in center of road as a POT with fence north. Stationing gives distance of 2599.6 to the NW corner and 2602.7 feet to the NE corner. Ties:

PP	NW	76.85
Cor FP	N	26.6

2009 Benton County Surveyor's Office set a ½ inch by 14 inch iron pipe cap No. 19552 on line and equal distant from the section corners measuring 5203.52 feet for the mile. This position is 2601.76 feet from both the northeast and northwest corner of the said section and fits the 1915 methods and measurement within 6 feet. The position falls 5 feet east of a field line to the north and fits the 1955 measurements within a foot.

County Coordinates
NAD 83 (1996 Adjustment)
N-164431.847
E-549902.190