

Statement of Evidence:

I041

North Quarter Corner of Section 4, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded:

12" Sugar	S 48 E	21 links
12" Sugar	N 13 W	9 links

1899 Road Survey Report by John E. Whilt, County Surveyor, shows survey running west to east on town line with a distance of 79.59 chains for the north line of Sec. 4, with no mention of the 1/4 corner.

1921 County Engineers' Notebook No. 39 shows survey of road on town line with stationing distances of 2622.4 feet to the NW corner and 2637.5 feet to the NE corner. Tie:

Cor. F. P.	S	18.5'
------------	---	-------

1955 County Engineer's Notebook No. 202 shows a survey of SAR 5 running west to east on town line. Corner is shown marked by a spike set in center of road with fence south. Stationing gives distance of 2622.7 feet to the NW corner and 2632.7 feet to the NE corner with a delta angle of 1-21' left. Ties:

TP	S	31.6'
Cor FP	SE	45.8'

Road south is 9 feet east and fence north is 13 feet east.

2001 Westwood Professional Services, Inc. found a PK at the intersection of County Road 5 (running east and west) and a fence line from the north. Removed PK and set cast iron monument at the location and established reference ties.

2002 Westwood Professional Services, Inc. notes the corner falls in line with road south to cemetery. Need to research cemetery for legal description and to see if we can find a survey.

DO NOT USE CIM!

County Coordinates
NAD 83 (1996 Adjustment)
N-
E-