

Statement of Evidence:

I363

East Quarter Corner of Section 36, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office surveyor, Theodore Conkey, set a wood post at this location and bearing trees were recorded.

8" Tamarac	N 15 W	43 links
8" Tamarac	S 62 E	24 links

Line trees were noted as a 8" Maple South 21.60 chains and a 8" Elm North 22.77 chains.

Undated County Surveyor's Record Book 2, page 456, notes the following B.T.
10" Bur Oak S 55 E 123 links

- 1996 John Oliver, LS 8194, Mille Lacs County Surveyor, set a 1" iron pipe at the lost position in a north/south road and filed a Certificate of Location (#244632). Note: distances from John Oliver & Associates to section corners = 2640.36.

- 2004 County Coordinates obtained by GPS

NAD 83 (1996 Adjustment)

N- 135460.551

E- 574000.088

- 2008 The County Surveyor's Office searched and found a 1/2" iron pipe approximately 0.3' below the surface at the centerline of road (170th Avenue N.W.) and on line with a found 1/2" iron pipe 30.0± feet to the east. Position gives a distance of 2640.53 feet to the NE 1/4 corner which agrees with the 1996 distance reported by Oliver of 2640.36 feet. Position falls 0°01'07" off of a straight line with the deflection angle (going south to north) falling left. The Surveyor accepts the position as the best evidence and updated ties.

County Coordinates to 1/2" iron pipe obtained by GPS

NAD 83 (1996 Adjustment)

N- 135460.385

E- 574000.510