

Statement of Evidence:

I353

East Quarter Corner of Section 35, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

- 1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" W Ash	N 75 W	14 links
13" Elm	S 60 1/2 E	20 links

- 1901 County Surveyor's Record Book A, Map No. 35, is a survey of Section 35 by John Whilt with a distance of 39.97 chains (2638.02 feet) to the NE corner Sec 35 and a distance of 38.96 chains (2571.36 feet) to the SE corner Sec 35.

- No Date County Surveyor's Record Book 2, page 454, notes a hub in the centerline of a road.

- 1930 County Engineer's notebook No. 58 shows road survey by H. G. Elletson running north to south. Corner is shown as a spike with ties:

F.P.	E	17.6'
F.P.	NE	23.7'

Stationing gives distances of 2638.7 feet to the NE corner and 2577.4 feet to the SE corner with a delta angle of 1-15' left.

- 2008 The County Surveyor's Office searched and found a PK Nail at centerline that was set by Dennis Taylor, LS (MN PLS #15233) at centerline of a north-south road (County Road 9) and on line with field lines running east and west. The County Surveyor's Office measured 2643.75 ft. to the NE Cor. and 2576.96 ft. to the SE Cor, which agree with the 1901 and 1930 measurements, above. The deflection angle measures (north to south) 1°08'53"- left, which compares well with the 1930 measurement of 1-15' left. The Surveyor accepts Taylor's position and set ties.

County Coordinates to PK obtained by GPS
NAD 83 (1996 Adjustment)
N-135351.430
E-568648.246