

Statement of Evidence:

I273

East Quarter Corner of Section 27, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

5" Tamarack	S 25 W	64 links
5" Tamarack	S 55 E	47 links

1902 County Surveyor's Record Book A, Map No. 32 shows a survey of Section 26 by John Whilt. Survey shows corner midway between section corners with a distance of 78.28 chains for the mile. Map No. 38 is a survey of Section 27 by John Whilt and shows the same distance with a note that the corner is a post under the north side of bridge.

No Date County Surveyor's Record Book 2, page 436, lists ties:

24" Elm	SW	83.6
8" Poplar	NW	42.0

2006 Benton County Surveyor's Office set a 1/2" x 14" iron pipe capped 19552 in the north-south centerline of 175th Ave. NE on fences east and west, fitting the lost position. The iron pipe measures 2593.38 to the section corners north and south, being 10 feet long per half mile of the 1902 measurements. This position agrees with the County Surveyor's Records in 1902 of the corner being located midway between section corners. The iron pipe is accepted as the best available evidence of the corner location.

County Coordinates
NAD 83 (1996 Adjustment)
N-140459.040
E-563340.474

2007 Benton County Surveyor's Office found a 1/2" iron pipe capped 19552 in the north-south centerline of 175th Ave. NE on fences east and west as set in 2006.